

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

800/800C Models Face of Wall Mounted

Slat Data

Series	Slat	Opening		
		Width	Standard	Optional
800	#14	Up to 15'4"	22 ga. steel	20,18 ga. Steel or 22,20 ga. stainless steel or .16 ga. (.050") B&S aluminum

*slats available with full fenestration or partial curtain fenestration
Slats are galvanized and painted or stainless steel (ss) or aluminum.

Series	Slat	Opening Width	Standard	Standard	Optional front
			front	back	
800C	#34	Up to 20'0"	22 ga. steel	24 ga. steel	20,18 ga. steel or 22,20 ga. stainless steel or 16 ga. (.050") B&S aluminum

STC

R-value	Rating
7.7	22

Slats are galvanized and painted or stainless steel (ss) or aluminum.

Headroom Clearance Dimensions

Slat	Opening	
	Height	Dimension A
#14	Thru 10'0"	18.5"
#14	Thru 15'0"	20"
#14	Thru 20'0"	22"
#34	Thru 6'0"	18.5"
#34	Thru 9'0"	20"
#34	Thru 14'0"	22"
#34	Thru 20'0"	*N/A

*Based on the door opening width of 10'0" wide

Sideroom Clearance Dimensions

Dimension C		Dimension D	
Drive Side	C	Non-Drive Side	D
	18"		12"

Side Room and Head Room

This door system requires a minimum of 12" on the non-drive side (9" if the cover is not used) and no less than 18" on the drive side (no less than 16" if the cover is not used). Base headroom requires a minimum of 15" up to 28" depending on head plate size. Add 2.5" for a hood.