






OPTIONS	
OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES

COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	LH BENCH MOUNT	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		




DOOR HEIGHT	DIM "A"
LESS THAN 6'-0"	33-7/8"
6'-0" OR GREATER AND LESS THAN 10'-0"	35-7/8"
10'-0" OR GREATER	37-7/8"

PROJECTION	
MIN.	MAX.
20" X 22"	32" X 34"


ROLLING STEEL

800FR FIRE RATED SHELTER DOOR


DWG. NO.	DATE:	Wayne Dalton
SHEET	BY:	



Z GUIDE DETAIL




MIXED GUIDE DETAIL




FULL SLAT SECTION HALF SLAT SECTION

OPTIONS

OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES




ELEVATION



SECTION A-A

MODEL	STANDARD MAX. VALUES	
	WIDTH	HEIGHT
800FR	11'	11'



SECTION B-B

DOOR HEIGHT	DIM "A"
LESS THAN 6'-0"	33'-7/8"
6'-0" OR GREATER AND LESS THAN 10'-0"	35'-7/8"
10'-0" OR GREATER	37'-7/8"

PROJECTION	
MIN.	MAX.
20" X 22"	32" X 34"

COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	RH BENCH MOUNT	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		

ROLLING STEEL

800FR FIRE RATED SHELTER DOOR




DWG. NO.	DATE:	
SHEET	BY:	

Z GUIDE DETAIL

MIXED GUIDE DETAIL

FULL SLAT SECTION HALF SLAT SECTION

OPTIONS	
OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES




COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	LH FRONT OF HOOD	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		


ROLLING STEEL

800FR FIRE RATED SHELTER DOOR


DWG. NO.	DATE:	
SHEET	BY:	



Z GUIDE DETAIL




MIXED GUIDE DETAIL




FULL SLAT SECTION HALF SLAT SECTION

OPTIONS

OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES




ELEVATION



SECTION A-A

MODEL	STANDARD MAX. VALUES	
	WIDTH	HEIGHT
800FR	11'	11'



SECTION B-B

DOOR HEIGHT	DIM "A"
LESS THAN 6'-0"	42-18"
6'-0" OR GREATER AND LESS THAN 10'-0"	44-1/8"
10'-0" OR GREATER	46-1/8"




PROJECTION	
MIN.	MAX.
20" X 22"	32" X 34"

COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	RH FRONT OF HOOD	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		

ROLLING STEEL




800FR FIRE RATED SHELTER DOOR

DWG. NO.	DATE:	
SHEET	BY:	



OPTIONS	
OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES

COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	LH TOP OF HOOD	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		



ROLLING STEEL

800FR FIRE RATED SHELTER DOOR




DWG. NO.	DATE:	Wayne Dalton
SHEET	BY:	

Z GUIDE DETAIL

MIXED GUIDE DETAIL

FULL SLAT SECTION HALF SLAT SECTION

OPTIONS	
OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES



COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	RH TOP OF HOOD	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		

ROLLING STEEL

800FR FIRE RATED SHELTER DOOR

DWG. NO.	DATE:	
SHEET	BY:	

Z GUIDE DETAIL



MIXED GUIDE DETAIL

FULL SLAT SECTION

HALF SLAT SECTION

OPTIONS

OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES






COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	LH WALL MOUNT	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		

ROLLING STEEL




800FR FIRE RATED SHELTER DOOR

DWG. NO.	DATE:	
SHEET	BY:	



OPTIONS	
OPENING WIDTH	
OPENING HEIGHT	
VOLTS OPTIONS	☐ 115-208-230V 1 PHASE 60HZ ☐ 208-230-460V 4 PHASE 60HZ ☐ 575V 3 PHASE 60HZ
GUIDE TYPE OPTIONS	☐ E GUIDES ☐ MIXED GUIDES ☐ Z GUIDES

COMPONENT	MATERIAL	OPERATION	NOTES:
HOOD	24 GA. GALVANIZED STEEL	RH WALL MOUNT	RATINGS: FEMA / ICC500 ULB 4HR FIRE RATING
CURTAIN	12 GA. GALVANIZED STEEL		
GUIDES	STEEL ANGLES		
BOTTOM BAR	STEEL ANGLES		



PROJECTION	
MIN.	MAX.
20" X 22"	32" X 34"

ROLLING STEEL

800FR FIRE RATED SHELTER DOOR

DWG. NO.	DATE:	The Genuine. The Original.
SHEET	BY:	