

Constructed from high-quality, kiln-dried western woods with a polystyrene insulation core, our flush-style wood door combines expert craftsmanship and durable materials to enhance your home's appeal while complementing a broad range of architectural designs.



DOOR CONSTRUCTION


EXTERIOR	INTERIOR	FRAME	TOTAL THICKNESS	PRIMING
3/8" Rough Sawn Ply-wood	1/4" Smooth Plywood	1-1/16"	1.6875"	Not Primed, Standard
5/8" T1-11 Plywood with 1/4" Grooves	1/4" Smooth Plywood	1-1/16"	1.9375"	Not Primed, Standard
1/4" Smooth Plywood	1/4" Smooth Plywood	1-1/16"	1.5625"	Not Primed, Standard
3/8" Marine Grade	1/4" Smooth Plywood	1-1/16"	1.6875"	Not Primed, Standard

- Distinctive exteriors to personalize your home
- Shiplap construction minimizes air infiltration
- Hand assembled
- External panels are pressure-bonded to framework with high-strength, waterproof adhesive

WOOD TYPES



Rough Sawn Plywood



T1-11 Plywood




Smooth Plywood



Marine Grade

Wood swatches shown have been treated with an after market stain. All doors will arrive unfinished.

WINDOWS



Cathedral*



Real Sunray



False Sunray*



2 Panel – 2 over 2




4 Panel – 2 over 2



2 Panel – 3 over 3



2 Panel – 4 over 4



2 Panel – 5 over 5

Windows shown for 1 car panel designs. Not all window will fit all door sizes.

Factory will advise if there is a problem with fitting.

**Molded designs with plastic inserts may not fit all panel sizes.*

Consult your distributor for availability.



Limited Warranty

The manufacturer warrants wood doors will be free from defects in material and workmanship for a period of one year from time of delivery.

Wayne Dalton

DISTRIBUTED BY:

2501 S. State Hwy. 121 Bus., Ste 200
Lewisville, TX 75067

wayne-dalton.com

