



Models 8300/8350/8500/8600(6600)/5150/5200

Option Code	Positive Design PSF	Negative Design PSF	Maximum Size		Facer Style Available ⁸	Approvals ³			Glazing available ⁶	Source Plant	Wind Speed ASCE 7-16 ASCE 7-22 (MPH) Exposure B ⁴	Wind Speed ASCE 7-16 ASCE 7-22 (MPH) Exposure C ⁵
			Width	Height		FBC	MDNOA	TDI ^{3*}				
2200	12.80	14.80	9'-2"	24'-0"	All	FL 10737	N/A	TPA - FL10737	Standard SP/LP	Mt. Hope	120	95
2201	19.10	20.60	9'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	140	115
2202	22.90	26.30	9'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	160	130
2203²	26.90	30.80	9'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	170	140
2204²	35.70	41.00	9'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	200	160
2205²	41.00	46.30	9'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	215	175
2206²	46.00	52.00	9'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	225	185
2300²	46.00	52.00	9'-2"	24'-0"	All	N/A	23-1120.14	N/A	Standard SP/LP, Impact SP/LP	Mt. Hope	225	185
2207²	64.00	72.00	9'-2"	24'-0"	All	FL 10737	N/A	TPA - FL10737	Impact SP/LP	Mt. Hope	265	215
2301²	64.00	72.00	9'-2"	24'-0"	All	N/A	23-1120.13	N/A	Impact SP/LP	Mt. Hope	265	215
2210	16.50	18.40	12'-2"	24'-0"	All	FL 10737	N/A	TPA - FL10737	Standard SP/LP	Mt. Hope	135	110
2211	19.30	21.60	12'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	145	120
2212²	22.40	25.10	12'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	160	130
2213²	25.70	28.80	12'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	170	140
2214²	33.10	37.00	12'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	195	155
2311²	46.00	52.00	12'-2"	24'-0"	All		23-1120.11		Standard SP/LP, Impact SP/LP	Mt. Hope	230	185
2240	12.40	13.80	16'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	120	95
2241	23.00	25.00	16'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	160	130
2242²	30.00	33.50	16'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	185	155
2243²	34.40	38.30	16'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	200	165
Post²	46.00	52.00	16'-2"	8'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	230	190
2341²	46.00	52.00	16'-2"	24'-0"	All		23-1120.10		Standard SP/LP, Impact SP/LP	Mt. Hope	230	190
2250	12.40	13.80	18'-2"	24'-0"	All		N/A		Standard SP/LP	Mt. Hope	120	100
2251²	23.00	25.00	18'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	160	130
2252²	30.00	33.50	18'-2"	24'-0"	All		N/A		N/A	Mt. Hope	185	155
2254²	30.00	33.50	18'-2"	24'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	185	155
Post²	46.00	52.00	18'-2"	8'-0"	All		N/A		Standard SP/LP, Impact SP/LP	Mt. Hope	230	190
2351²	46.00	52.00	18'-2"	24'-0"	All	23-1120.12	Standard SP/LP, Impact SP/LP	Mt. Hope	230	190		
2260	15.45	16.79	22'-2"	24'-0"	All	N/A	Standard SP/LP	Mt. Hope	135	110		
2261	20.15	22.50	22'-2"	24'-0"	All	N/A	N/A	Mt. Hope	155	125		

[Post Installation Instructions 10737](#)
[Jamb Connection Supplement FL 10737](#)
[Track Supplement Chart FL 10737](#)

1. All doors tested for uniform static air pressure per ANSI/DASMA 108 or TAS 202 to test pressure of 1.5 x design pressure or Miami-Dade TAS 202
2. Also tested for large missile impact and cyclic wind pressure per ANSI/DASMA 115 and/or TAS 201/203
3. FBC - Florida Building Commission, MDNOA - Miami Dade Notice of Acceptance, TDI - Texas Department of Insurance
[*TDI now use 3rd Party Evaluations. For WD, TDI's link points to the FBC evaluation report.](#)
4. Wind Speed is 3-Second Peak gusts, using exposure B, for single or double story structures, calculated according to ASCE 7-22.
5. Wind Speed is 3-Second Peak gusts, using exposure C, for single or double story structures, calculated according to ASCE 7-22.
Assumptions: Mean roof height of 25 ft, flat ground, sea level, enclosed building and roof angle >10°.
The Wind Speed Calculation is based on the max width of the door and a max height of 8-7 ft depending on the section heights.
If a narrower, or taller door is used instead of the max shown in the chart, the wind speed rating may be different.
For reference only. Final door requirements to be determined by architect, engineer or other professional.
6. **Standard SP/LP** - Short, vertical, and long panel glazing is not impact resistant and does not meet the requirements for Wind-Borne Debris Regions.
Standard SP - Short and vertical panel glazing is not impact resistant and does not meet the requirements for Wind-Borne Debris Regions.
Impact SP/LP - Short, vertical, and long is impact resistant and does meet the requirements for Wind-Borne Debris Regions.
7. Low Head Room track is available.
8. All - Vertical Panel, Flush, Short Panel, Vertical Long Panel, and Long Panel.
9. Wind speeds listed in this guide are provided for reference purposes only. In **ALL** cases the local building authority is the sole and final determiner of the structural and safety requirements, and suitability of the garage door.
10. Model 8500/5200 is **NOT** available with Impact Glazing